PARTNERTECH

1144 Budapest, Gvadányi u. 61-65., „A” épület
+36 1 433 0100
+36 20 407 24 72 – műszaki telefonszám

DATASHEET



AI673

REMOTE INDICATOR WITH ACOUSTIC

MAIN FEATURES

- REMOTE INDICATOR WITH ACOUSTIC

TECHNICAL SPECIFICATIONS

Power supply	
Power supply type	VDC
Operating voltage	6 to 28 VDC
Current consumption	4 mA nominal7.5 mA at 28 VDC
Inputs / outputs	
Output level	80 dB @ 10 cm
Output level adjustment	No
Physical characteristics	
Cable size	0.75 to 1.5 mm²
Colour	Red
Physical dimensions	80 x 30 x 80 mm (W x H x L)
Net weight	± 55 g
Mounting type	Base mount
Mounting position	Ceiling, Wall
Mounting base	Shallow
Material	Polycarbonate (self-extinguishing)
Environmental characteristics	
Operating temperature	−5 to +40°C
Storage temperature	−20 to +50°C
Relative humidity	10 to 95% (noncondensing)

PARTNERTECH

1144 Budapest, Gvadányi u. 61-65., „A” épület
+36 1 433 0100
+36 20 407 24 72 – műszaki telefonszám

AI673

TECHNICAL SPECIFICATIONS

Environment	Indoor
IP rating	IP30
Other characteristics	
Compatibility	Aritech 700/2000 & Kidde Excellence series devices
Monitoring	Unmonitored
Number of connection terminals	5
Frequency	4 kHz
Selectable tones	1
Synchronization	Not supported
Rating	200 µcd
Flash frequency	±1.3 Hz±78 flashes/min
Texture	Textured
Vandal proof	No
Compliancy	CE, REACH, RoHS 3, WEEE
Certification	CE